

## Requirements for an Internet Printing Protocol

### STATUS OF THIS MEMO

This document is an Internet-Draft. Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

To learn the current status of any Internet-Draft, please check the "lid-abstracts.txt" listing contained in the Internet-Drafts Shadow Directories on ftp.is.co.za (Africa), nic.nordu.net (Europe), munnari.oz.au (Pacific Rim), ds.internic.net (US East Coast), or ftp.isi.edu (US West Coast).

### ABSTRACT

This document is one of a set of documents which together describe all aspects of a new Internet Printing Protocol (IPP). IPP is an application level protocol that can be used for distributed printing on the Internet. The protocol is heavily influenced by the printing model introduced in the Document Printing Application (ISO/IEC 10175 DPA) standard. Although DPA identifies the both end user and administrative features, IPP is initially focused only on the end user functionality.

The full set of IPP documents include:

- Internet Printing Protocol/1.0: Requirements
- Internet Printing Protocol/1.0: Model and Semantics
- Internet Printing Protocol/1.0: Security
- Internet Printing Protocol/1.0: Protocol Specification
- Internet Printing Protocol/1.0: Directory Schema

This document describes the requirements for an Internet printing protocol. It describes the end-user, operator and administrator wants and needs in the context of printing documents from a variety of sources. These sources include standard desktop applications (e.g. word processors, spreadsheets, and browsers), documents selected by reference (e.g. URL) and documents created by batch or background applications. Additionally, requirements for light-weight printer status and management and job status and management services will be discussed.

## TABLE OF CONTENTS

1. TERMINOLOGY .....	5
2. REQUIREMENTS .....	6
2.1. END-USER.....	6
2.1.1. Finding or locating a printer.....	6
2.1.2. Create an instance of the printer.....	7
2.1.3. Viewing the status of a printer.....	7
2.1.4. Submitting a print job.....	8
2.1.5. Viewing the status of a submitted print job.....	9
2.1.6. Canceling a Print Job.....	9
2.2. OPERATOR.....	9
2.2.1. Alerting.....	10
2.2.2. Changing Print and Job Status.....	10
2.3. ADMINISTRATOR.....	10
3. IPP SCENARIOS .....	12
3.1. PRINTER DISCOVERY.....	13
3.2. DRIVER INSTALLATION.....	14
3.3. SUBMITTING A PRINT JOB.....	14
3.4. GETTING STATUS/CAPABILITIES.....	15
3.5. ASYNCHRONOUS NOTIFICATION.....	16
3.6. JOB CANCELING.....	16
4. OBJECTIVES OF THE PROTOCOL .....	18
4.1. SECURITY.....	18
4.2. INTERACTION WITH LPD (RFC1179).....	18
4.3. EXTENSIBILITY.....	19
4.4. FIREWALLS.....	19
4.5. INTERNATIONALIZATION.....	20
5. REFERENCES .....	21
6. ACKNOWLEDGMENTS .....	21
7. AUTHOR'S ADDRESS .....	21
8. APPENDIX - DETAILED SCENARIOS .....	22
8.1. PRINTER DISCOVERY WITHIN AN ENTERPRISE.....	22
8.2. PRINTER DISCOVERY ACROSS ENTERPRISES.....	24
8.3. PRINTER DISCOVERY ON THE INTERNET -LOGICAL OPERATIONS...	25
8.4. PRINTER DISCOVERY ON THE INTERNET - AUTHENTICATION.....	26
8.5. DRIVER DOWNLOAD.....	28
8.6. SUBMITTING A PRINT JOB AS A FILE.....	29
8.7. SUBMITTING A PRINT JOB WITH TWO DOCUMENTS.....	30
8.8. SUBMITTING A PRINT JOB AS A FILE, PRINTING FAILS.....	31
8.9. SUBMITTING A PRINT JOB WITH AUTHENTICATION, PRIVACY AND PAYMENT.....	32
8.10. SUBMITTING A PRINT JOB WITH DECRYPTION ERROR.....	33
8.11. SUBMITTING A PRINT JOB WITH AUTHENTICATION.....	35
8.12. SUBMITTING A PRINT JOB GENERATED DYNAMICALLY.....	36

- 8.13. SUBMITTING A PRINT JOB WITH A PRINTER JAM - CANCELED... 37
- 8.14. SUBMITTING A PRINT JOB WITH A PRINTER JAM - RECOVERED.. 38
- 8.15. SUBMITTING A PRINT JOB WITH SERVER PULL..... 39
- 8.16. SUBMITTING A PRINT JOB WITH REFERENCED RESOURCES..... 40
- 8.17. GETTING CAPABILITIES..... 41
  - 8.17.1. Submission Attributes ..... 41
  - 8.17.2. Printer Capabilities ..... 41
- 8.18. GETTING STATUS..... 42
  - 8.18.1. Printer State/Status ..... 42
  - 8.18.2. Job Status ..... 42
  - 8.18.3. Status of All My Jobs ..... 42
- 8.19. ASYNCHRONOUS NOTIFICATION..... 44
  - 8.19.1. Job Completion ..... 44
  - 8.19.2. Job Complete with Data ..... 44
  - 8.19.3. Print Job Fails ..... 44
- 8.20. CANCEL A JOB..... 45
- 8.21. END TO END SCENARIO - WITHIN AN ENTERPRISE..... 46
- 8.22. END TO END SCENARIO - ACROSS ENTERPRISES..... 48
- 8.23. END TO END SCENARIO - ON THE INTERNET..... 51

## 1. TERMINOLOGY

Internet Printing for the purposes of this document is the application of World Wide Web tools, programs, servers and networks to allow end-users to print to a remote printer using, after initial setup or configuration, the same methods, operations and paradigms as would be used for a locally attached or a local area network attached printer. This could include the use of HTTP servers and browsers for providing static, dynamic and interactive printer locating services, user installation, selection, configuration, [print job submission](#), [printer capability inquiry](#) and status inquiry of remote printers and jobs.

For the purposes of this document, a WEB Browser is software available from a number of sources including but not limited to the following: Microsoft Internet Explorer, NCSA Mosaic, Netscape Navigator, Sun Hot Java!. The major task of these products is to use the Hypertext Transport Protocol (HTTP) to retrieve, interpret and display Hypertext Markup Language (HTML).

Throughout this document, 'printer' shall be interpreted to include any device which is capable of marking on a piece of media using any available technology. No assumption is made about multi-tiered printing solutions involving servers (single or multiple) logically in front of the actual printing device and all such configurations shall be supported but shall appear to the end-user as only a single device.

Throughout this document, certain requirements will be identified as not being a part of version 1.0 (or V1.0) of the protocol [or as being satisfied by means outside of IPP. For example printer instance creation is not performed by but is enabled by the protocol](#). Globally, none of the operator or administrators requirements will be included in version 1.0. Some of the end-user requirements may also be excluded from version 1.0 and will be so noted in the description of that requirement. Subsequent versions of the protocol (e.g. V2.0) may include support for these initially excluded requirements.

## 2. REQUIREMENTS

The next three sections identify the requirements of an Internet printing protocol from three roles assumed by humans: end-user, operator, and administrator. The requirements defined here are only those that need to be addressed by an application level Internet printing protocol. Other requirements, such as that the operator needs physical access to the printer ([e.g. to be able to load paper or clear jams](#)) are not covered by this document.

Section 3 contains scenarios which provide more detailed examples of the entire process including discovery, status, printing and end-of-job reporting.

### 2.1. END-USER

An end-user of a printer accepting jobs through the Internet is one of the roles in which humans act. The end-user is the person that will submit a job to be printed on the printer.

The requirements of the end-user are broken down into six categories: finding/locating, local instance, viewing printer status, [viewing printer capabilities](#), submitting a print job, viewing job status, altering the [attributes](#) of a print job.

#### 2.1.1. Finding or locating a printer.

end-users want to be able to find and locate printers to which they are authorized to print. They want to be able to perform this function using a standard WEB browser or other application. Multiple criteria can be applied to find the printers needed. These criteria include but are not limited to:

- by name (Printer 1, Joes-color-printer, etc.)
- by geographic location (bldg 1, Kentucky, etc.)
- by capability or attribute (color, duplex, legal paper, etc.)

Additionally, end-users want to be able to limit the scope of their searching to:

- inside a functional sub-domain
- include only a particular domain (lexmark.com)
- exclude specified domains

### 2.1.2. Create an instance of the printer.

After finding the desired printer, an end-user needs to be able to create a local instance of that printer within the end-user operating system or desktop. This local instance will vary depending upon the printing paradigm of the operating system. For example, some UNIX users will only want a queue or a reference to a remote printer created on their machine while other UNIX users and Windows NT users will want the queue and also the necessary icons and registry entries to be created and initialized. Where required, drivers may need to be downloaded from some repository and installed on the computer. All necessary decompressing, unpacking, and other installation actions should occur without end-user interaction or intervention excepting initial approval by the end-user. Once the local instance of the printer has been installed, it shall appear to the end-user of operating system and to the applications running there as any other printer (local, local area network connected, or network operating system connected) on the end-user desktop or environment. [An Internet Printing Protocol's role in this requirement is to enable \(by providing configuration information, driver location, etc.\) the creation of the printer instance rather than the actual creation of the printer instance.](#)

### 2.1.3. Viewing the status [and capabilities](#) of a printer.

Before using a selected printer or, in fact at any time, the end-user needs the ability to verify the characteristics and status of both printers and jobs queued for that printer. When checking the characteristics of a printer, the end-user typically wants to be able to determine the capability of the device, e.g.:

- loaded media, commonly paper, by size and type
- paper handling capability, e.g. duplex, collating, finishing
- color capability

When checking the status of the printer, the end-user typically wants to be able to determine:

- is the printer on-line?
- what are the defaults to be used for printing?

When checking the status on jobs queued for the printer, the end-user typically wants to be able to determine:

- how many jobs are queued for the printer?
- how are job priorities assigned?

#### 2.1.4. Submitting a print job.

Once the desired printer has been located and installed, the end-user wants to print to that printer from normal applications using standard methods. These normal applications include such programs as word processors, spreadsheets, data-base applications, WEB browsers, [production printing applications](#), etc. In addition to printing from an application, the end-user needs to have the ability to submit a print job by reference. Printing by reference is defined to mean as submitting a job by providing a reference to an existing document. The reference, a URL, will be resolved before the actual print process occurs.

Some means shall be provided to determine if the format of a job matches the capability of the printer. This can be done by one of the following:

- the end-user selects the correct printer driver
- the printer automatically selects the proper interpreter
- the end-user uses some other manual procedure.

A standard action shall be defined should the job's requirements not match the capabilities of the printer.

Because the end-user does not want to know the details of the underlying printing process, the protocol must support job-to-printer capability matching (all implementations are not necessarily required to implement this function.) This matching capability requires knowing both the printer's capabilities and attributes and those capabilities and attributes required by the job. Actions taken when a print job requires capabilities or attributes that are not available on the printer vary and can include but are not limited to:

- rejecting the print job
- redirecting the print job to another printer



- printing the job, accepting differences in the appearance

Print jobs will also be submitted by background or batch applications without human intervention. Any application level Internet printing application must support this type of printing.

end-users need the ability to set certain print job parameters at the time the job is submitted. These parameters include but are not limited to:

- number of copies
- single or two sided printing
- finishing
- job priority

#### 2.1.5. Viewing the status of a submitted print job.

After a job has been submitted to a printer, the end-user needs a way to view the status of that job (i.e. job waiting, job printing, job done) and to determine where the job is in the print queue.

In addition to the need to inquire about the status of a print job, automatic notification of the completion of that job is also required. New notification means are not defined by the protocol but the protocol must provide a means of enabling and disabling the notification.

#### 2.1.6. Canceling a Print Job

While a job is waiting to be printing or has been started but not yet completed, the original creator/submitter of the print job (i.e. the end-user) shall be able to cancel the job entirely (job is waiting) or the remaining portion of it (job is printing.) Altering the print job itself is not a V1.0 requirement.

### 2.2. OPERATOR

An operator of a printer accepting jobs through the Internet is one of the roles in which humans act. The operator has the responsibility of monitoring the status of the printer as well as managing and controlling the jobs at the device. These responsibilities include but are not limited to the replenishing of supplies (ink, toner, paper, etc.), the clearing of minor errors (paper jams, etc.) and the re-prioritization of end-user jobs. Operator requirements will not be addressed by V1.0 of the protocol.

The requirements of the operator include all those of the end-user but may include additional privileges. For example, an operator may be able to view all print jobs on a printer while the end-user may only see his own jobs.

#### 2.2.1. Alerting.

One of the required operator functions is having the ability to discover or to be alerted to changes in the status of a printer particularly those changes that cause a printer to stop printing and to be able to correct those problems. As such, an Internet printing protocol shall be able to alert a designated operator or operators to these conditions such as 'out of paper', 'out of ink', etc. Additionally, the operator shall be able to, asynchronous to other printer activity, inquire as to a printer's or a job's status.

#### 2.2.2. Changing Print and Job Status.

Another of the required operator functions is the ability to affect changes to printer and job status remotely. For example, the operator will need to be able to re-prioritize or cancel any print jobs on a printer to which the operator has authority.

### 2.3. ADMINISTRATOR

An administrator of a printer accepting jobs through the Internet is one of the roles in which humans act. The administrator has the responsibility of creating the printer instances and controlling the authorization of other

end-users and operators. Administrator requirements will not be addressed by V1.0 of the protocol.

The requirements of the administrator include all those of the end-user and, in some environments, some or all of those of the operator. Minimally, the administrator must also have the tools, programs, utilities and supporting protocols available to be able to:

- create an instance of a printer
- create, edit and maintain the list of authorized end-users
- create, edit and maintain the list of authorized operators
- create, edit and maintain the list of authorized administrators
- create, customize, change or otherwise alter the manner in which the status capabilities and other information about printers and jobs are presented
- create, customize, or change other printer or job features
- administrate billing or other charge-back mechanisms
- create sets of defaults
- create sets of capabilities

The administrator must have the capability to perform all the above tasks locally or remotely to the printer.

### 3. IPP SCENARIOS

Each of the scenarios in this section describes a specific IPP operation, such as submitting a print job. Section 8.0 contains several detailed flows for each scenario to provide additional detail. The examples should not be considered exhaustive, but illustrative of the functions and features required in the protocol. Flows are intended to be protocol neutral. It is not assumed that all of the functions and features described in these scenarios will necessarily be supported directly by IPP or in version 1.0 of IPP.

These scenarios support one of three physical configurations:

- An IPP client talking to an IPP Printer object imbedded in a single, physical output device.
- An IPP Client talking to a server containing one or more IPP Printer objects. Each Printer object is associated with exactly one physical output device supported by the server. The protocol between the server and the output devices is undefined.
- An IPP Client talking to an IPP Printer object in a server. The Printer object is associated with one or more physical output devices, but the client only sees the Printer object, which is an abstraction and represents all of the associated physical output devices. The protocol between the server and the physical output devices is undefined.

Clients and Printers may or may not be behind firewalls, i.e. not directly on the Internet. At least the following should be considered:

- Client and Printer are behind the same firewall.
- Client is behind one firewall and Printer is behind another.
- Client is behind a firewall and Printer is not.
- Printer is behind a firewall and the client is not.
- Neither Client nor Printer are behind a firewall.

See draft-ietf-ipp-security-01.txt for more details on these and other configurations of clients, servers and firewalls.

### 3.1. PRINTER DISCOVERY

Client  
Service

Directory  
Service

```
+----->
  give me information on printers with these characteristics

<-----+
  Information on Printers matching these characteristics
```

The objective of printer discovery is to locate printers that meet the client's requirements. The directory Service should provide enough information for the client to make an initial choice. The client may have to connect to each individual Printer offered to get more detail.

The actual protocol used between client and Directory or Name service is considered outside the scope of IPP. Printer Discover is included in the scenarios to provide requirements for the directory schema for IPP Printers and to further define Printer attributes.

Characteristics that might be considered when locating a Printer include:

- capabilities of the Printer, e.g. PDLs supported
- physical location, e.g. in building 010
- driver required and location
- cost per page to print
- whether or not printer is access controlled
- whether or not usage requires client authentication
- whether or not Printer can be authenticated
- whether or not payment is required for printing
- maximum job size (spool size)
- whether or not Printer support compression
- whether or not Printer supports encryption
- administrative limits on this Printer
  - maximum number of copies per job
  - maximum number of pages per job

Responses could additionally include:

- how to get more information
  - web page
  - telephone number
  - help desk

### 3.2. DRIVER INSTALLATION

Client	Printer
+----->	
Where can I find a driver & software to install it?	
<-----+	
URLs for drivers and install software	

Driver here refers to the code installed in the client operating system to generate the print data stream for the intended printer. The actual details for installing a printer driver are operating system independent and are beyond the scope of IPP. However, an IPP printer or a directory service advertising an IPP Printer should be capable of telling a client what drivers are required, where they can be found, and provide pointers to installation instructions, installation code or initialization strings required to install the driver.

### 3.3. SUBMITTING A PRINT JOB

Client	IPP Printer
+----->	
Here is a Print Job	
- Job and document attributes	
- Print data	
<-----+	
Response	



- State of all jobs owned by this client
  - queued
  - printing
  - completed
- Job submission attributes supported/required
  - scheduling attributes (e.g. priority)
  - production attributes (e.g. number of copies)

3.5. ASYNCHRONOUS NOTIFICATION

```
ClientIPP Printer

+----->
  Use the following method to notify me of Printer events
      .
      .
      .
<-----+
```

Asynchronous notification of Printer event

Clients must be able to request asynchronous notification for Printer events such as

- job completion
- a fatal error that requires the job to be resubmitted
- a condition that severely impacts a queued job for this client  
  e.g. printer is out of paper

Note: end-user notification is a V1.0 requirement while operator notification is for V2.0.

3.6. JOB CANCELING

```
ClientIPP Printer

+----->
  Modify the named job as indicated
```



< -----+  
Response (did it or not)

Clients must be able to make changes to jobs which have been submitted and are queued for printing. Changing of job attributes should also be supported. Job modifications, holding and releasing of jobs will not be required in IPP v1.0.

#### 4. OBJECTIVES OF THE PROTOCOL

The protocol to be defined by an Internet printing working group will address the requirements of the end-user (V1.0). It will not, at least initially, address the operator or administrator requirements (V2.0).

The protocol defined shall be independent of the operating system of both the client and the server. Any platform [capable of supporting](#) a WEB Browser shall be supported as a client. Any platform providing a WEB/HTTP server and printing services shall be supported as a server. Usage of the WEB Browser and Server is not required for IPP; the operating system, operating system extensions or other applications may provide IPP functionality directly.

In many environments such as Windows 95, Windows NT and OS/2, the print data is created and transmitted to the printer 'on the fly' rather than being created, spooled and then transmitted to the printer (a typical UNIX method.) The Internet Printing Protocol must properly handle this methodology and make this transparent to the end-user.

##### 4.1. SECURITY

Security definitions, issues and requirements are discussed in a separate draft. See 'draft-ietf-ipp-security-00.txt' for these requirements. Authentication shall be required in V1.0. [Privacy, payment, and other aspects of security are not required for V1.0.](#)

##### 4.2. INTERACTION WITH LPD (RFC1179)

Many versions of UNIX and in fact other operating systems provide a means of printing as described in RFC1179 (Line Printer Daemon Protocol.) This document describes the file formats for the control and data files as well as the messages used by the protocol. Because of the simplistic approach taken by this protocol, many manufacturers have include proprietary enhancements and extensions to 'lpd.' Because of this divergence and due to other requirements described in this document, there

is no requirement for backward compatibility or interoperability with 'lpd'. However, a mapping of LPD functionality and IPP functionality shall be provided so as to enable a gateway between LPD and IPP.

#### 4.3. EXTENSIBILITY

The Internet Printing Protocol shall be extensible by several means that facilitates interworking and prevents implementation collisions:

- by providing a process whereby implementers can submit proposals for registration of new attributes, new enumerated values for existing attributes and new tags for attributes or attribute values
- that require review and approval. The Internet Assigned Number Authority (IANA) will be the repository for such accepted registration proposals after review.
- that do not require review and approval. IANA will be the repository for such registrations.
- by providing syntax in the protocol so that implementers may add private (i.e. unregistered) attributes, enumerated attribute values, and tags.
- by providing versioning and negotiation so as to enable future implementations of IPP to interoperate with implementations of version 1.0 of IPP.

#### 4.4. FIREWALLS

As stated in the end-user requirements section, Internet printing shall by definition support printing from one enterprise to another. As such, the Internet printing protocol must be capable of passing through firewalls and/or proxy servers (where enabled by the firewall administrator) preferably without modification to the existing firewall technology.

#### 4.5. INTERNATIONALIZATION

Users of Internet printing will come from all over the world. As such, where appropriate, internationalization and localization will be enabled for the protocol.

## 5. REFERENCES

RFC1179 - Line Printer Daemon Protocol  
RFC1759 - Printer MIB  
ISO/IEC 10175, Document Printing Application

## 6. ACKNOWLEDGMENTS

This document draws heavily from preliminary work done by others especially in the Printer Working Group (PWG). The author gratefully acknowledges the specific contributions of:

Scott Isaacson  
Novell  
scott\_isaacson@novell.com

Roger Debry  
IBM  
rdebry@us1.ibm.com

Carl-Uno Manros  
Xerox  
manros@cp10.es.xerox.com

Robert Herriot  
Sun  
Robert.Herriot@eng.sun.com

Tom Hastings  
Xerox  
hastings%cp10.es.xerox.com

Peter Zehler  
Xerox  
Peter\_Zehler@wb.xerox.com

## 7. AUTHOR'S ADDRESS

F.D. (Don) Wright  
Lexmark International  
C14/035-3  
740 New Circle Rd  
Lexington, KY 40511

Phone: 606-232-4808  
Fax: 606-232-6740  
E-mail: don@lexmark.com

## 8. APPENDIX - DETAILED SCENARIOS

The following are more detailed scenarios illustrating how the Internet Printing Protocol is expected to be used. The information contained herein is meant to be generic. There may not be an exact wording or terminology match between these scenarios and the implementation documents.

8.1. PRINTER DISCOVERY WITHIN AN ENTERPRISE

A user wants to find a color Postscript printer in his/her enterprise which will print transparencies. The client, directory service, and Printer are all behind the same corporate firewall. Because color foils are expensive, Printers of this type are access controlled and require an account to be established so that printing can be billed back to the using department. Note the request to find a Printer usable by Dept. J15. Drivers for all supported Printers are available from the server they are associated with. A help desk is provided for end user support. The printer is unattended.

Client

Directory Service

```
+-----+ >
  Find a Printer with these characteristics
  - prints color, prints transparencies
  - prints Postscript
  - is in building 003
  - usable by department J15
<-----+
Printer "Color-A"
- prints color, prints transparencies
- prints Postscript
- in room H-6, building 003
- driver ABC-Postscript-V1.3 required, here is URL
- cost is $.45 per page for color transparencies
- limit is 10 pages per job
- authentication required to use printer
- printer is unattended
- help desk at x5001
```

Wright

draft-ietf-ipp-req-00.txt

[Page 22]

Expires: Sept 24, 1997

## Printer "Color-B"

- prints color, prints transparencies
- prints Postscript
- in room J-10, building 003
- driver XYZ-Postscript-V2.4 required, here is URL
- cost is \$1.25 page for color transparencies
- limit is 5 pages per job
- authentication is required to use printer
- printer is unattended
- help desk at x5001

## 8.2. PRINTER DISCOVERY ACROSS ENTERPRISES

A user in Company A wants to find a public printer in a business partner's enterprise (Company B) on which to print a purchase order. The client is behind one corporate firewall and the directory service and the Printer are behind a different corporate firewall. Drivers for all supported Printers are available from the server they are associated with. A web page is provided for end user support for public printers.

Client

Company B Directory Service

```
+----->
  Find a Printer with these characteristics
  - prints black and white
  - is in El Segundo, building A
  - is a public printer (accessible from outside firewall)
<-----+
Printer "Public-A"
- prints black and white
- prints Postscript
- in El Segundo, room H-6, building A
- driver ABC-Postscript-V1.3 required, here is URL
- printer is public
- help available at http://xerox/elSegundo/publicPrinters

Printer "Public-B"
- prints black and white
- prints PCL/5e
- is in El Segundo, room J-10, building A
- driver XYZ-PCL-V2.4 required, here is URL
- printer is public
- help available at http://xerox/elSegundo/publicPrinters
```

Wright

draft-ietf-ipp-req-00.txt

[Page 24]

Expires: Sept 24, 1997



8.3. PRINTER DISCOVERY ON THE INTERNET -LOGICAL OPERATIONS

A student wants to print a paper on a printer at his neighborhood Kinko's print shop. The report was written using Microsoft Word. The student is interested in the cost of printing since his budget is limited. Note the use of logical operators to find this information.

Client

Kinko's Directory Service

```
+----->
  Find a Printer with these characteristics
  - prints color or black and white
  - costs less than $.50 per page
  - tell me about resolution and marking technology

<-----+
Printer "Color-A"
- prints color
- 600 dpi laser printer
- prints Postscript
- driver ABC-Postscript-V1.3 required, here is URL
- cost is $.50 per page for color
- payment required prior to submitting print job
- here is URL for more information on Kinko's

Printer "Mono-B"
- prints black and white
- 300 dpi inkjet printer
- prints Postscript
- driver XYZ-Postscript-V2.4 required, here is URL
- cost is $0.35 page for black and white
- payment required prior to submitting print job
- here is URL for more information on Kinko's
```

Wright

draft-ietf-ipp-req-00.txt

[Page 25]

Expires: Sept 24, 1997

8.4. PRINTER DISCOVERY ON THE INTERNET - AUTHENTICATION

An executive in her hotel room is finishing an important presentation on her laptop computer. She connects to a local print shop through the web to get a copy of her charts printed for tomorrow's presentation. She must find a print shop that is convenient to her hotel and can print color transparencies. She wants to be sure that the printer can be authenticated and can accept encrypted data.

Client

SirSpeedy Directory Service

+-----&gt;

Find a Printer with these characteristics

- prints color transparencies
- is in Downtown Boulder, Colorado
- Printer can be authenticated
- Printer supports encryption

Give me the Printer's public key

Tell me when you are open for business

&lt;-----+

Printer "Color-A"

- prints color transparencies
- prints Postscript
- driver ABC-Postscript-V1.3 required, here is URL
- payment required prior to submitting print job
- Printer can be authenticated
- Data can be encrypted
- Printer's public key = "CG&89Hj\$#004?"
- Located at 1670 Pearl Street, Boulder, CO
- This Branch is open 24 hours a day

Printer "Color-B"

- prints color transparencies
- prints Postscript
- driver ABC-Postscript-V1.3 required, here is URL
- payment required prior to submitting print job

Wright

draft-ietf-ipp-req-00.txt

[Page 26]

Expires: Sept 24, 1997

- Printer can be authenticated
- Data can be encrypted
- Printer's public key = "CG&7%%j\$#003"
- Located at 1220 Arapahoe, Boulder, CO
- This Branch is open from 9:00am to 6:30pm

### 8.5. DRIVER DOWNLOAD

An end user in an enterprise wants to print a lengthy report on a newly installed high speed PostScript printer. Since she will likely use this printer often, she would like to download a driver and install it on her workstation. She is running Windows 95. Note: Driver download is not a V1.0 requirement.

Client

IPP Printer

```
+----->
  Tell me where to find print drivers for you
  I am using Windows 95 version 1.2

<-----+
  Driver install file is at
  http://www.ibm.com/drivers/NP12a/Win95
```

### 8.6. SUBMITTING A PRINT JOB AS A FILE

An end-user wants to submit a print job. The print file already exists on his workstation. The client and Printer are behind the same corporate firewall. The printer is available to anyone behind the firewall and no authorization or authentication is required. The data is pushed to the Printer. The Printer is capable of spooling the output. No errors occur.

Client

IPP Printer

```
+----->
Here is a print job
- job name = MyJob
- notify me by email when done printing
- print on iso-a4-white paper
- print on both sides of the paper
- return status of the printer in response
- document is in Postscript format
- here is the document to print

<-----+
```

```
Print job accepted and spooled
- job id = #12345
- current state of print job = spooled
- submission time = 02/12/97, 15:35
- printer state = printing
```

### 8.7. SUBMITTING A PRINT JOB WITH TWO DOCUMENTS

An end-user wants to submit a print job. The print file already exists on his workstation. The client and Printer are behind the same corporate firewall. The printer is available to anyone behind the firewall and no authorization or authentication is required. The data is pushed to the Printer. The job consists of two separate documents. The Printer is capable of spooling the output. No errors occur.

Client

IPP Printer

```
+----->
Here is a print job
- job name = MyJob
- notify me by email when done printing
- print on iso-a4-white paper
- print on both sides of the paper
- return status of the printer in response
- document #1 is in Postscript format
- here is the document to print
- document #2 is in Postscript format
- here is the document to print

<-----+
Print job accepted and spooled
- job id = #12345
- current state of print job = spooled
- submission time = 02/12/97, 15:35
- printer state = printing
```

Wright

draft-ietf-ipp-req-00.txt  
Expires: Sept 24, 1997

[Page 30]

8.8. SUBMITTING A PRINT JOB AS A FILE, PRINTING FAILS

An end-user wants to submit a print job. The print file already exists on his workstation. The client and Printer are behind the same corporate firewall. The printer is available to anyone behind the firewall and no authorization or authentication is required. The data is pushed to the Printer. The Printer is not capable of spooling the output so it begins printing while still receiving the file. An error occurs and the printer cannot complete printing (in this case the user requires A4 paper and that paper size is not available on the printer.)

Client

IPP Printer

```
+----->
Here is a print job
- job name = MyJob
- notify me by email when done printing
- print on iso-a4-white paper
- print on both sides of the paper
- return status of the printer in response
- document is in Postscript format
- here is the document to print

<-----+
Print job accepted - printing failed - current state of
print job = canceled (A4 not available)
- submission time = 02/12/97, 15:35
- printer state = ready
```

Wright

draft-ietf-ipp-req-00.txt  
Expires: Sept 24, 1997

[Page 31]

### 8.9. SUBMITTING A PRINT JOB WITH AUTHENTICATION, PRIVACY AND PAYMENT

A traveling executive needs to print a set of transparencies for an important business meeting. The charts are in Lotus Freelance format on his notebook computer. He has located a SirSpeedy print shop near his hotel that will print color transparencies. Because the information on the charts is sensitive, he wants to be sure that his data is sent to the Printer in an encrypted format. He also wants to authenticate the Printer. The Printer also authenticates the user. Payment occurs across the Internet.

```
Client      IPP Printer  +-----+
----->
< -----+
    Mutual authentication and exchange of secret keys

+----->
    Here is a print job
    - job name = MyJob
    - notify me by email when done printing
    - print on iso-a4-white paper
    - print on both sides of the paper
    - return status of the printer in response
    - tell me where to pick up output
    - document is in Postscript format
    - here is the document to print (encrypted)

< -----+
    Print job accepted and spooled
    - job id = #12345
    - current state of print job = spooled
    - submission time = 02/12/97, 15:35
    - printer state = printing
    - payment required to proceed with job
    - pick up at 230 East Main after 3:30pm today

+----->
< -----+
    Payment transaction
```



8.10. SUBMITTING A PRINT JOB WITH DECRYPTION ERROR

A traveling executive needs to print a set of transparencies for an important business meeting. The charts are in Lotus Freelance format on his notebook computer. He has located a SirSpeedy print shop near his hotel that will print color transparencies. Because the information on the charts is sensitive, he wants to be sure that his data is sent to the Printer in an encrypted format. He also wants to authenticate the Printer. The Printer also authenticates the user. Payment occurs across the Internet. An error occurs during decryption.

Client

IPP Printer

```
+----->
<-----+
  Mutual authentication and exchange of secret keys

+----->
  Here is a print job
  - job name = MyJob
  - notify me by email when done printing
  - print on iso-a4-white paper
  - print on both sides of the paper
  - return status of the printer in response
  - tell me where to pick up output
  - document is in Postscript format
  - here is the document to print (encrypted)

<-----+
  Print job accepted and spooled
  - job id = #12345
  - current state of print job = spooled
  - submission time = 02/12/97, 15:35
  - printer state = printing
  - payment required to proceed with job
  - pick up at 230 East Main after 3:30pm today

+----->
<-----+
  Payment transaction
```

Wright

draft-ietf-ipp-req-00.txt

[Page 33]

Expires: Sept 24, 1997

```
.  
. .  
. .  
< -----+  
Asynchronous response (email in this case)  
- decryption failed on job #12345  
- no pages printed  
- current state of job = aborted
```

8.11. SUBMITTING A PRINT JOB WITH AUTHENTICATION

An end-user wants to submit a print job. The print file already exists on his workstation. The client and Printer are behind the same corporate firewall. The printer is available to anyone behind the firewall but authentication and authorization is required. Authorization takes place using the authenticated end-user's name. The data is pushed to the Printer. The Printer is capable of spooling the output.

Client

IPP Printer

```
+----->
< -----+
  Authentication
```

Note: An authentication failure would end the transaction at this point.

```
+----->
Here is a print job
- job name = MyJob
- notify me by email when done printing
- print on iso-a4-white paper
- print on both sides of the paper
- return status of the printer in response
- tell me where to pick up output
- document is in Postscript format
- here is the document to print

< -----+
Print job accepted and spooled
- job id = #12345
- current state of print job = spooled
- submission time = 02/12/97, 15:35
- printer state = printing
```

Wright

draft-ietf-ipp-req-00.txt  
Expires: Sept 24, 1997

[Page 35]

8.12. SUBMITTING A PRINT JOB GENERATED DYNAMICALLY

An end-user wants to submit a print job. The print data is generated dynamically and is being transmitted by a printer driver on the client workstation as available. The client and Printer are behind the same corporate firewall. The printer is available to anyone behind the firewall and no authentication and authorization is required. The data is pushed to the Printer. The Printer is capable of spooling the output. No error occurs.

Client

IPP Printer

```
+----->
Here is a print job
- job name = MyJob
- notify me by email when done printing
- print on iso-a4-white paper
- print on both sides of the paper
- return status of the printer in response
- document is in Postscript format
- here is the print job

<-----+
Print data accepted and spooling started
- job id = #12345
- current job state = spooled
- submission time = 02/12/97, 15:35
- printer state = printing
```

Wright

draft-ietf-ipp-req-00.txt  
Expires: Sept 24, 1997

[Page 36]

8.13. SUBMITTING A PRINT JOB WITH A PRINTER JAM - CANCELED

An end-user wants to submit a print job. The print data is generated dynamically and is being transmitted by a printer driver on the client workstation as available. The client and Printer are behind the same corporate firewall. The printer is available to anyone behind the firewall and no authentication and authorization is required. The data is pushed to the Printer. The Printer is not capable of spooling the output. The printer jams notifies the user and the user chooses to cancel the job.

```
Client                                                    IPP Printer
+-----+-----+
Here is a print job
- job name = MyJob
- notify me by email when done printing
- print on iso-a4-white paper
- print on both sides of the paper
- return status of the printer in response
- document is in Postscript format
- here is the document to print

< -----+
Print data accepted and printing started
- job id = #12345

+-----+-----+
- What is the status of print job #12345?

< -----+
- Job #12345 accepted but printer jammed, cannot continue

+-----+-----+
- Cancel job #12345

* Printer flushes remaining data
< -----+
Print job terminated
- current job state = canceled
- submission time = 02/12/97, 15:35
- printer state = jammed
```

8.14. SUBMITTING A PRINT JOB WITH A PRINTER JAM - RECOVERED

An end-user wants to submit a print job. The print data is generated dynamically and is being transmitted by a printer driver on the client workstation as available. The client and Printer are behind the same corporate firewall. The printer is available to anyone behind the firewall and no authentication and authorization is required. The data is pushed to the Printer. The Printer is not capable of spooling the output. The printer jams, notifies the user and the user clears the jam and elects to continue.

Client

IPP Printer

```
+----->
Here is a print job
- job name = MyJob
- notify me by email when done printing
- print on iso-a4-white paper
- print on both sides of the paper
- return status of the printer in response
- document is in Postscript format
- here is the document to print

<-----+
Print data accepted and printing started
- job id = #12345

<-----+
- Notification: printer jammed, cannot continue

* Jam is clear by human intervention, printing continues

+----->
Here is the last part of the document to print

<-----+
Print job received
- current job state = printing
- submission time = 02/12/97, 15:35
- printer state = printing
```

Wright

draft-ietf-ipp-req-00.txt

[Page 38]

Expires: Sept 24, 1997

8.15. SUBMITTING A PRINT JOB WITH SERVER PULL

An end-user wants to submit a print job. The print data is in a file and is publicly available. It is pulled by the Printer. The client and Printer are behind the same corporate firewall. The printer is available to anyone behind the firewall and no authentication and authorization is required. The Printer is capable of spooling the output. Printing may start before the entire job has been pulled.

Client

IPP Printer

```
+----->
Here is a print job
- job name = MyJob
- notify me by email when done printing
- print on iso-a4-white paper
- print on both sides of the paper
- return status of the printer in response
- here is a reference to the data to be printed

<-----+
Print data accepted and printing started
- job id = #12345
- current state of job = spooled
- submission time = 02/12/97, 13:15
- printer state = printing

.
.
<-----+
Get the file to be printed

+----->
Here it is

Note: Failure to find the file, would end the transaction
      with an error at this point and an asynchronous
      notification would be send to the Client.

<-----+
Data received
```

Wright

draft-ietf-ipp-req-00.txt  
Expires: Sept 24, 1997

[Page 39]

### 8.16. SUBMITTING A PRINT JOB WITH REFERENCED RESOURCES

An end-user wants to submit a print job. The print data is on a file on the user's workstation. It is pushed by the client, but printing requires some resources not included in the print file, e.g. a high resolution image or a font resource. Printer. The client and Printer are behind the same corporate firewall. The printer is available to anyone behind the firewall and no authentication and authorization is required. The Printer is capable of spooling the output. No errors occur.

Client

IPP Printer

```
+----->
Here is a print job
- job name = MyJob
- notify me by email when done printing
- print on iso-a4-white paper
- print on both sides of the paper
- return status of the printer in response
- external resource required - here is URL
- here is the data to be printed
  - (with an external data reference)

<-----+
Print data accepted and printing started
- job id = #12345
- current state of job = spooled
- submission time = 02/12/97, 13:15
- printer state = printing

.
.
<-----+
Get the external resource

+----->
Here it is
```

Wright

draft-ietf-ipp-req-00.txt  
Expires: Sept 24, 1997

[Page 40]



8.17. GETTING CAPABILITIES

## 8.17.1. Submission Attributes

An end-user wants to get the production and scheduling attributes that are supported or required when submitting jobs to this Printer. The client will use these attributes when forming the subsequent print request.

```
Client                                     IPP Printer
+-----+-----+
I'm going to submit a Postscript job
give me your job submission attributes

< -----+
Postscript production attributes for this Printer are:
- medium-select = us-letter-white, us-legal-white
  - default is us-letter-white
  - copies = 1,2,3,4,5
  - default is 1
    - print-quality = draft, normal, high
    - default is draft
    - sides = 1-sided, 2-sided-long-edge
    - default is 2-sided-long-edge
- Job scheduling attributes for this Printer are:
  - job-priority = 1,2,3
  - default = 3
```

## 8.17.2. Printer Capabilities

An end-user wants to determine the resolution, marking technology, and PDLs supported by the printer.

```
Client                                     IPP Printer
+-----+-----+
Please tell me the
- resolution of the printer
- the marking technology of the printer
- PDLs supported

< -----+
Printer resolution = 600 dpi
Marking Technology = laser
PDLs supported = Postscript level 2, PCL/6
```

## 8.18. GETTING STATUS

### 8.18.1. Printer State/Status

An end-user wants to determine the state or status of the printer.

Client

IPP Printer

```
+----->
  What is the state of the printer?
<-----+
```

```
Printer state = out-of-paper
```

### 8.18.2. Job Status

An end user wants to get the status of a job he has submitted.

Client

IPP Printer

```
+----->
  Please tell me the status of job #12345
<-----+
```

```
Job #12345 is queued
it is number 3 in the queue
printer state = printing
```

### 8.18.3. Status of All My Jobs

An end user wants to get a list of all of the jobs he has submitted to this Printer.

Client

IPP Printer

```
+----->
  Please tell me the status of my jobs
```

< -----+  
Job #00012 is complete  
Printed at 12:35 on 01/23/97  
  
Job #09876 is printing  
  
Job #12345 is queued  
it is number 3 in the queue  
  
Job #34567 is queued  
it is number 7 in the queue



8.20. CANCEL A JOB

The end-user submits a print job and later decides to cancel it.

Client

IPP Printer

```
+----->
< -----+
  Authentication.

+----->
  Cancel job #1234

< -----+
  Job #1234 Canceled
```

8.21. END TO END SCENARIO - WITHIN AN ENTERPRISE

An office worker prints on shared departmental printers. All printers in the office are public, that is, no authentication or authorization is required. Printers are protected from external access by a firewall. No billing or accounting is required. Most printing is done from desktop applications. A help desk is provided for printing problems. Standard operating systems and applications are used. Drivers are available, but are installed manually by support personnel. This scenario assumes that drivers have been installed and that drivers are not IPP aware, that is, they cannot communicate across an IPP connection to obtain status and capabilities. IPP printers appear in application pull-down menus. Printer configuration data is hard wired into the driver.

Client

IPP Printer

End-user selects print from the application pull down menu. An IPP printer is selected from the list of Printers offered

The driver puts up a dialogue with hard-wired set of options for this printer. The end-user makes choices and submits job.

```
+----->
  Here is a print job
  - job-name = memo-to-boss
  - notify me by email when job is complete
  - print on us-letter-white paper
  - print 1 copy
  - print at normal quality
  - print on 1 side
  - give me the state of the printer in response
```

The driver generates the print data and passes it to the IPP driver a piece at a time as it is generated.

```
+----->
  Here is the print data

<-----+
  Print data received, file is spooled
```

Wright

draft-ietf-ipp-req-00.txt

[Page 46]

Expires: Sept 24, 1997

- printer state = printing
- time submitted = 2/12/97, 15:35
- current job state = spooled

Client adds this job to list of current jobs. List of jobs and state of each is available on a pull-down menu on the client.

End-user selects job #1234 from list and clicks on it to see its status.

```
+----->
  Give me the state of job #1234
  and the state of the Printer

< -----+
```

Job #1234 state = spooled

- it is number 3 in the queue
- printer state = printing

The job completes without error

```
< -----+
```

Job #1234 completed  
12 of 12 pages printed





End-user selects print from the application pull down menu.  
"Public-A" is selected from the list of Printers offered

```
+----->
  I'm going to submit a print job
  give me your job submission attributes

<-----+
  Production attributes for this Printer are:
  - medium-select = us-letter-white, us-legal-white
    - default is us-letter-white
    - copies = 1,2,3,4,5
    - default is 1
      - print-quality = draft, normal, high
    - default is draft
      - sides = 1-sided, 2-sided-long-edge
    - default is 2-sided-long-edge

  Job scheduling attributes for this Printer are:
  - job-priority = 1,2,3
    default = 3
```

Driver puts up dialogue with available options and fills in the defaults.

End-user makes choices and submits job

```
+----->
  Here is a print job
  - job-name = memo-to-Don-Wright
  - notify me by email when job is complete
  - print on us-letter-white paper
  - print 1 copy
  - print at normal quality
  - print on 1 side
  - give me the state of the printer in response
```

The driver generates the print data and passes it to the IPP driver a piece at a time.

```
+----->
  Here is the print data

<-----+
```

Print data received, and spooling started  
print job id = #1234

Print data received, file is spooled

- printer state = printing
- time submitted = 2/12/97, 15:35
- current job state = spooled

Client adds this job to list of current jobs. List of jobs and state of each is available on a pull-down menu on the client.

End-user selects job #1234 from list and clicks on it to see its status.

```
+----->
  Give me the state of job #1234
  and the state of the Printer

< -----+
  Job #1234 state = spooled
  - it is number 3 in the queue
  - printer state = printing

* The job completes without error
< -----+
```

8.23. END TO END SCENARIO - ON THE INTERNET

An executive in her hotel room is finishing an important presentation on her laptop computer. She connects to a local print shop through the web to get a copy of her charts printed for tomorrow's presentation. She must find a print shop that is convenient and can print color transparencies. She must download and temporarily install a driver in order to generate the PDL required by the print shop. Mutual authentication is required by the printshop and payment must be made in advance. The job is encrypted on the wire to prevent eavesdropping.

End-user completes presentation. She goes to the web and connects to the SirSpeedy home page.

```
Client                               SirSpeedy Directory Service
+----->
```

```
Find me a printer with these characteristics
- Near Market Street in San Jose
- Prints color transparencies
- drivers can be downloaded
- supports privacy (encryption)
- takes my VISA card
- give me rough cost per page
```

Available Printers matching these characteristics are looked up in the Directory Service

```
< -----+
```

```
Printer "Color-A"
- located at 123 First Street in San Jose
- URL is http://www.SirSpeedy.com/FirstStreet/Color-A
- prints color transparencies
- 600 dpi laser
- driver ABC-Postscript-V1.3 available at this URL
- cost = $.75 per page
- authentication required to use printer
- payment required prior to printing
- printer's public key = " !@8778961"
```

```
Printer "Color-B"
```

- located at 67 San Carlos Street, San Jose
- URL is <http://www.SirSpeedy.com/SanCarlos/Color-B>
- prints color transparencies
- 1200 dpi laser
- driver XYZ-Postscript-V4.3 available at this URL
- cost = \$1.25 per page
- authentication required to use printer
- payment required prior to printing
- printer's public key = "!@#%\$78961"
- more information at this URL

The user decides to use the first printer because it is closer. She connects to the URL given to get a driver.

Client	Driver URL
+----->	
I need a driver for "Color-A"	
I am using Windows 95	
<-----+	
Driver installation files	
Driver is installed	
User connects to	
"Color-A"	

Client	IPP Printer "Color-A"
+----->	
<-----+	
Mutual authentication and exchange of secret keys	
+----->	
I'm going to submit a print job	
give me your job submission attributes	
<-----+	
Production attributes for this Printer are:	
- medium-select = us-letter-white, us-legal-white	
- default is us-letter-white	
- copies = 1,2,3,4,5	
- default is 1	
- print-quality = draft, normal, high	

- default is draft
- sides = 1-sided, 2-sided-long-edge
  - default is 2-sided-long-edge

Job scheduling attributes for this Printer are:

- job-priority = 1,2,3
  - default = 3

Driver puts up dialogue with available options and fills in the defaults.

End-user makes choices and submits job

```
+----->
  Here is a print job
  - job-name = presentation
  - notify me by email when job is complete
  - print on us-letter-transparency
  - print 1 copy
  - print at high quality
  - print by 9:00 am tomorrow morning
  - give me the state of the printer in response
```

The driver generates the print data and passes it to the IPP driver a piece at a time.

```
+----->
  Here is the print data

< -----+
  Print data received, and spooling started
  print job id = #1234

  Print data received, file is spooled
  - printer state = printing
  - time submitted = 2/12/97, 15:35
  - current job state = held, waiting for payment

+----->
< -----+
  Payment transaction

< -----+
  Job is scheduled to print, pick up after 9:00am tomorrow
  Thank you for using SirSpeedy
```